

> DATASHEET


FLUSH CASEMENT WINDOW



FEATURES

- > **ELEGANT AESTHETICS**
Slim and modern aluminium frames with sightlines starting from just 74mm
- > **ENERGY EFFICIENT**
70mm deep thermally broken frame achieves U-Values as low as 1.5 W/m²K with a double glazed unit, and a B-C rating on the BFRC WER scheme
- > **HEIGHTENED SECURITY**
Features multi-point locking system, PAS 24 and Secured By Design Certified, and in compliance with Part Q of the building regulations
- > **FLEXIBLE CONFIGURATIONS**
Choose from top hung, side hung, dummy sash, egress and easy clean options
- > **GLAZING OPTIONS**
Internal Glazed with 28mm glazing thickness
- > **CHOICE OF FINISH**
Available in any single RAL colour, dual colour, textured or an anodised finish

TECHNICAL DRAWINGS



SIZE & WEIGHT LIMITS

Top Hung	
Max Size (mm)	1400w x 1200h
Min Size (mm)	352w x 352h
Max Weight	35kg
Side Hung	
Max Size (mm)	700w x 1400h
Min. Size (mm)	352w x 352h
Max Weight	26kg
Fixed Light	
Max Weight	250kg

PERFORMANCE

U-Value (Double Glazing)	(U _g : 1.0 W/m²K) 1.5 W/m²K
U-Value (Triple Glazing)	1.2 W/m²K
Window Energy Rating (WER)	B-C
BRE Green Guide Rating	A rated
Air Permeability	Class 4 (600 Pa)
Water Tightness	Class 9a (600pa)
Wind Resistance	Class E2400 (2400 Pa)
Acoustic Performance Rw	Rw (C;Ctr) 42 (-1;-5) dB
Security	PAS 24 & SBD
3rd Party Certification Q Mark	✓
BUILDING REGULATIONS	
Part L	Compliant
Part F	Compliant
Part M	Compliant
Part Q	Compliant

SIGHTLINES

Head	74mm
Cill	99mm
Jamb	74mm
Mullion	112mm

FINISHES

Single Colour	✓
Dual Colour	✓
Textured Finish	✓
Anodised Finish	✓

DETAILS

Frame Depth	70mm
Glazing Thickness	28mm